

## Product sheet

# CONEXT NEWPRO ANCHOR FOR STATIC LIFELINES

**L'ECHELLE**  
EUROPEENNE

**L'ECHELLE EUROPEENNE EXCLUSIVE**

## DESCRIPTION

**Multifunctional anchor made up of a stainless steel plate and a ready-to-install matrix.**

The matrix benefits from specific machining, allowing the cable to be oriented on each side.

It is versatile and can be used both as entry or exit anchorage point as well as an intermediate point.

The energy absorbed by sliding offers very low figures.

## TECHNICAL FEATURES

- Stainless steel plate, aluminium matrix

| Reference       | Definition                                   | Weight (kg) |
|-----------------|----------------------------------------------|-------------|
| <b>A0015000</b> | CONEXT NEWPRO<br>Anchor for static lifelines | 1,230       |



### BENEFITS

This versatile tool can be used for entry, exit and intermediate points.



| Resistance      |                                                                         |
|-----------------|-------------------------------------------------------------------------|
| Number of users | 5 people simultaneously                                                 |
| Mass            | 1.230 kg                                                                |
| Installation    | To be anchored on OMEGA MINI, OMEGA, concrete, wood or metal structures |

## ASSEMBLY PROCEDURE

1. Check the condition of the anchor support and the cable.
  2. Place the plate on the surface.
  3. Position the 10 mm lifeline cable inside the aluminium matrix using the 6 bolts.
- They should be tightened all the way onto the plate using high-strength thread sealant.

## INSTALLATION RECOMMENDATIONS

Important: the hook must be able to pass freely.

The lifespan of the equipment depends on the quality of the surface and the environment.

A check is required at least every 12 months.

|           |                                                                          |
|-----------|--------------------------------------------------------------------------|
| Plate     | STAINLESS STEEL NEWPRO 80                                                |
| Material  | 316L stainless steel                                                     |
| Matrix    | MAC NEWPRO                                                               |
| Material  | Aluminium                                                                |
| Bolts     | 6 10*25 stainless steel bolts                                            |
| Fastening | Tightened all the way onto the plate using high-strength thread sealant. |