

DESCRIPTION

Horizontal and vertical junction piece to consolidate movements and limit handling errors.

Operators are always completely safe, as they are never required to detach from the lifeline.

It allows for ascents/descents to be coupled with horizontal lifelines. No disconnection.

TECHNICAL FEATURES

- Set of 3 316L stainless steel/Aluminium pieces

Reference	Definition	Weight (kg)
A0015002	CONEXT RUPT Breaking system for static lifelines	2,430



Set of 3 pieces	Static lifeline breaking system
Material	316L stainless steel/Aluminium
Mass	2.430 kg

ASSEMBLY PROCEDURE

1. Check the condition of the anchor support and the cable.
2. RUPT is a kit made up of 3 pieces: entry/middle/exit.
3. The entry/exit points are fixed using the brackets supplied or using 10 mm stainless steel quick links connected to cable loops behind a piece of the lifeline. The middle piece attaches to the automatic fall arrest device. The middle piece must be connected to the fall arrest system using a quick link. The user must also be connected to the fall arrest system by way of a carabiner.

INSTALLATION RECOMMENDATIONS

Dedicated instructions are available for the RUPT. RUPT pieces must be serviced annually in our workshops or those of our partner distributors.

The lifespan of the equipment depends on the quality of the surface and the environment.

Wear may be increased in certain environments (snow, ice, salty environments).